


ľ	DIST	COUNTY	ROUTE	KILOMETER POS TOTAL PROJEC		TOTAL				
ric		Pal	CH							
	REGISTERED CIVIL ENGINEER S PROFESS JONAL									
				Si Po	ul Cotte	18				
		I y I, I	999		34509					
	The S	ate of Califo	rnia or its off		9-30-99 CIVIL					
	agents or con sheet.	shall not be in opteteness of	responsible for electronic copie	the accuracy states of this plan	OF CAL SECON	*/				

TABLE B

TIMBER STRUTS FOR STRUCTURAL STEEL PLATE VEHICULAR UNDERCROSSING					
SPAN (mm)	STRUT SIZE (mm)	SILL SIZE (mm)			
4013 - 4724	89×89	89×I40			
4800 -5258	89×89	89×184			
Over 5258	140×140	140×184			

Tabular data in Table B based on 152x51mm corrugations, (Structural steel plate)



SECTION B-B







TABLE A

TIMBER STRUTS FOR STRUCTURAL STEEL PLATE PIPE								
PIPE DIA (mm)	STRUT STZE (mm)	HEIGHT OF FILL						
6100 Thru	184×184	I.5 m SPACING	I.O m SPACING					
6400	235×235	2.5 m SPACING	I.4 m SPACING					





STRUCTURAL STEEL PLATE PIPES



TYPICAL SECTION

STRUCTURAL STEEL PLATE ARCHES

Struts required when span of structural steel plate arch exceeds 5.5 m. Pad size as directed by Engineer.

NOTES

- Struts shown are minimum required during construction and are for earth loads only.
- Backfill shall be brought up uniformly on both sides of the structure.
- For minimum cover over structure for construction loads, see Standard Plan D88.

STATE OF CALIFORNIA
DEPARTMENT OF TRANSPORTATION

STRUT DETAILS FOR STRUCTURAL STEEL PIPES, ARCHES AND VEHICULAR UNDERCROSSING

NO SCALE

ALL DIMENSIONS ARE IN MILLIMETERS UNLESS OTHERWISE SHOWN

D88A